Roto
Window & Door
Technology

Roto Patio Lift

Invitation of tenders



Roto Patio Lift is the hardware for versatile use in aluminium and PVC Lift&Slide systems with sash weights from 150 to 400 kg, which is also suitable for modern Slim profiles.

- Lift&Slide system with Slim versions for narrow profiles.
- DesignLocking: espagnolette with locking cam and associated striker.
- Stainless steel Plus version for increased corrosion protection requirements.
- Quiet operation and outstanding running properties thanks to high-quality roller unit technology:
  - Ball-bearing-mounted rollers
  - Quiet bogies
- Durability thanks to the use of robust materials:
  - Rollers made from high-quality PVC
  - Roller unit side panels made from stainless steel
- Night ventilation is possible in conjunction with optional locking pin.
- Accessory: info clip for individual branding.
- SH:SW = max. 2.5:1
- Sash width: max. 3000 mm
- Sash height: max. 3100 mm
- Sash weight: max. 400 kg
- Sash arrangement according to diagrams A, C, D, F, G and K
- Operating range: -20 °C to +50 °C

Application ranges:

- Roto Patio Lift:
  - Sash Rebate Width: 720 – 3000 mm
  - Sash Rebate Height: 1000 – 3100 mm
  - Sash weight: up to max. 400 kg *
  - Handle Height: fixed
  - Security levels: according to DIN EN 1627-1630

Products:

Roto Patio Lift or equivalent.

Key:

* The application ranges are to be adhered according to the application diagrams in the installation manuals.
* Compliance with the areas of application specified by system manufacturers.

Roto Frank N.V./S.A.
Window and door technology
Raam- en deurtechnologie
Technologie pour fenêtres et portes

Ikaroslaan 14
1930 Zaventem
Belgium

info.ewe@roto-frank.com
www.roto-frank.com

Roto Frank Limited
Window and door technology

Postal address
71 Knowl Piece
Wilbury Way, Hitchin
Hertfordshire
SG4 0TY
United Kingdom